

# Lucene Tutorial

borrowing from: Chris Manning and Pandu Nayak

# Open source IR systems

---

- Widely used academic systems
  - Terrier (Java, U. Glasgow) <http://terrier.org>
  - Indri/Galago/Lemur (C++ (& Java), U. Mass & CMU)
  - Tail of others (Zettair, ...)
- Widely used non-academic open source systems
  - **Lucene**
    - Things built on it: Solr, ElasticSearch
  - A few others (Xapian, ...)

# Lucene


---

- Open source Java library for indexing and searching
  - Lets you add search to your application
  - Not a complete search system by itself
  - Written by Doug Cutting
- Used by: Twitter, LinkedIn, Zappos, CiteSeer, Eclipse, ...
  - ... and many more (see <http://wiki.apache.org/lucene-java/PoweredBy>)
- Ports/integrations to other languages
  - C/C++, C#, Ruby, Perl, Python, PHP, ...

# Based on “Lucene in Action”

---

By Michael McCandless, Erik Hatcher, Otis Gospodnetic




Covers Lucene 3.0.1. It's now up to 6.2.1

# Resources

---

- Lucene: <http://lucene.apache.org>
- Lucene in Action: <http://www.manning.com/hatcher3/>
  - Code samples available for download
- Ant: <http://ant.apache.org/>
  - Java build system used by “Lucene in Action” code  
(downloadable from Lucene in Action website)

# Lucene in a search system



# Lucene demos

---

- Source files in `lia2e/src/lia/meetlucene/`
  - Actual sources use Lucene 3.0.1
  - Code in these slides upgraded to Lucene 6
- Command line **Indexer**
  - `lia.meetlucene.Indexer`
- Command line **Searcher**
  - `lia.meetlucene.Searcher`

# Core indexing classes

---

- **IndexWriter**
  - Central component that allows you to create a new index, open an existing one, and add, remove, or update documents in an index
  - Built on an `IndexWriterConfig` and a `Directory`
- **Directory**
  - Abstract class that represents the location of an index
- **Analyzer**
  - Extracts tokens from a text stream

# Creating an IndexWriter

---

```
Import org.apache.lucene.analysis.Analyzer;
import org.apache.lucene.index.IndexWriter;
import org.apache.lucene.index.IndexWriterConfig;
import org.apache.lucene.store.Directory;
...
private IndexWriter writer;

public Indexer(String dir) throws IOException {
    Directory indexDir = FSDirectory.open(new File(dir));
    Analyzer analyzer = new StandardAnalyzer();
    IndexWriterConfig cfg = new IndexWriterConfig(analyzer);
    cfg.setOpenMode(OpenMode.CREATE);
    writer = new IndexWriter(indexDir, cfg)
}
```

# Core indexing classes (contd.)

---

- **Document**
  - Represents a collection of named **Fields**. Text in these **Fields** are indexed.
- **Field**
  - **StringFields** are indexed but not tokenized
  - **TextFields** are indexed and tokenized

# A Document contains Fields

# Index a Document with IndexWriter

---

```
private IndexWriter writer;  
...  
private void indexFile(File f) throws  
    Exception {  
    Document doc = getDocument(f);  
    writer.addDocument(doc);  
}
```

# Indexing a directory

---

```
private IndexWriter writer;  
...  
public int index(String dataDir,  
                  FileFilter filter)  
    throws Exception {  
    File[] files = new File(dataDir).listFiles();  
    for (File f: files) {  
        if (... &&  
            (filter == null || filter.accept(f))) {  
            indexFile(f);  
        }  
    }  
    return writer.numDocs();  
}
```

# Closing the IndexWriter

---

```
private IndexWriter writer;  
...  
public void close() throws IOException {  
    writer.close();  
}
```

# The Index

---

- The Index is the kind of inverted index we know and love
- default Lucene codec includes term frequencies and positional information
- APIs to customize the codec


# Core searching classes

---

- **IndexSearcher**
  - Central class that exposes several search methods on an index
  - Accessed via an **IndexReader**
- **Query**
  - Abstract query class. Concrete subclasses represent specific types of queries, e.g., matching terms in fields, boolean queries, phrase queries, ...
- **QueryParser**
  - Parses a textual representation of a query into a **Query** instance

# IndexSearcher

---



# Creating an IndexSearcher

---

```
import org.apache.lucene.search.IndexSearcher;  
...  
public static void search(String indexDir,  
                         String q)  
    throws IOException, ParseException {  
    IndexReader rdr =  
        DirectoryReader.open(FSDirectory.open(  
            new File(indexDir)));  
    IndexSearcher is = new IndexSearcher(rdr);  
    ...  
}
```

# Query and QueryParser

---

```
import org.apache.lucene.queryParser.flexible.standard.StandardQueryParser;  
import org.apache.lucene.search.Query;  
...  
public static void search(String indexDir, String q)  
    throws IOException, ParseException  
...  
StandardQueryParser parser =  
    new StandardQueryParser(new StandardAnalyzer());  
Query query = parser.parse(q, "contents");  
...  
}
```

# Core searching classes (contd.)

---

- **TopDocs**
  - Contains references to the top documents returned by a search
- **ScoreDoc**
  - Represents a single search result

# search( ) returns TopDocs

---

```
import org.apache.lucene.search.TopDocs;  
...  
public static void search(String indexDir,  
                         String q)  
    throws IOException, ParseException  
...  
IndexSearcher is = ...;  
...  
Query query = ...;  
...  
TopDocs hits = is.search(query, 10);  
}
```

# TopDocs contain ScoreDocs

---

```
import org.apache.lucene.search.ScoreDoc;  
...  
public static void search(String indexDir, String q)  
    throws IOException, ParseException  
...  
IndexSearcher is = ...;  
...  
TopDocs hits = ....;  
...  
for(ScoreDoc scoreDoc : hits.scoreDocs) {  
    Document doc = is.doc(scoreDoc.doc);  
    System.out.println(doc.get("fullpath"));  
}  
}
```

# Closing IndexSearcher

---

```
public static void search(String indexDir,  
                         String q)  
    throws IOException, ParseException  
  
...  
  
IndexSearcher is = ...;  
  
...  
  
is.close();  
}
```

# How Lucene models content

---

- A Document is the atomic unit of indexing and searching
  - A Document contains Fields
- Fields have a name and a value
  - You have to translate raw content into Fields
  - Examples: Title, author, date, abstract, body, URL, keywords, ...
  - Different documents can have different fields
  - Search a field using name:term, e.g., title:ucene

# Fields

---

- Fields may
  - Be indexed or not
    - Indexed fields may or may not be analyzed (i.e., tokenized with an Analyzer)
      - Non-analyzed fields view the entire value as a single token (useful for URLs, paths, dates, social security numbers, ...)
  - Be stored or not
    - Useful for fields that you'd like to display to users

# Field construction

## Lots of different constructors

---

```
import org.apache.lucene.document.Field  
import org.apache.lucene.document.FieldType
```

```
Field(String name,  
      String value,  
      FieldType type);
```

value can also be specified with a Reader, a TokenStream, or a byte[ ].

FieldType specifies field properties.

Can also directly use sub-classes like TextField, StringField, ...

# Using Field properties

---

Index	Store	Example usage
NOT_ANALYZED	YES	Identifiers, telephone/SSNs, URLs, dates, ...
ANALYZED	YES	Title, abstract
ANALYZED	NO	Body
NO	YES	Document type, DB keys (if not used for searching)
NOT_ANALYZED	NO	Hidden keywords

# Analyzer

---

- Tokenizes the input text
- Common Analyzers
  - `WhitespaceAnalyzer`  
Splits tokens on whitespace
  - `SimpleAnalyzer`  
Splits tokens on non-letters, and then lowercases
  - `StopAnalyzer`  
Same as `SimpleAnalyzer`, but also removes stop words
  - `StandardAnalyzer`  
Most sophisticated analyzer that knows about certain token types, lowercases, removes stop words, ...

# Analysis example

---

- “The quick brown fox jumped over the lazy dog”
- **WhitespaceAnalyzer**
  - [The] [quick] [brown] [fox] [jumped] [over] [the] [lazy] [dog]
- **SimpleAnalyzer**
  - [the] [quick] [brown] [fox] [jumped] [over] [the] [lazy] [dog]
- **StopAnalyzer**
  - [quick] [brown] [fox] [jumped] [over] [lazy] [dog]
- **StandardAnalyzer**
  - [quick] [brown] [fox] [jumped] [over] [lazy] [dog]

# Another analysis example

---


- “XY&Z Corporation – xyz@example.com”
- WhitespaceAnalyzer
  - [XY&Z] [Corporation] [-] [xyz@example.com]
- SimpleAnalyzer
  - [xy] [z] [corporation] [xyz] [example] [com]
- StopAnalyzer
  - [xy] [z] [corporation] [xyz] [example] [com]
- StandardAnalyzer
  - [xy&z] [corporation] [xyz@example.com]

# What's inside an Analyzer?

- Analyzers need to return a `TokenStream`
- this is an abstract class, with subclasses  
**Tokenizer** and **TokenFilter**

```
public TokenStream tokenStream(String fieldName,
```

```
          Reader reader)
```



Tokenizer input is a Reader, and TokenFilter input is a TokenStream

# Tokenizers and TokenFilters

---

- **Tokenizer**
  - WhitespaceTokenizer
  - KeywordTokenizer
  - LetterTokenizer
  - StandardTokenizer
  - ...
- **TokenFilter**
  - LowerCaseFilter
  - StopFilter
  - PorterStemFilter
  - ASCIIFoldingFilter
  - StandardFilter
  - ...

# Adding/deleting Documents to/from an IndexWriter

---

```
long addDocument(Iterable<IndexableField> d);
```

IndexWriter's Analyzer is used to analyze document.

Important: Need to ensure that Analyzers used at indexing time are consistent with Analyzers used at searching time

```
// deletes docs containing terms or matching  
// queries. The term version is useful for  
// deleting one document.
```

```
long deleteDocuments(Term... terms);
```

```
long deleteDocuments(Query... queries);
```

# Index format

---

- Each Lucene index consists of one or more segments
  - A segment is a standalone index for a subset of documents
  - All segments are searched
  - A segment is created whenever `IndexWriter` flushes adds/deletes
- Periodically, `IndexWriter` will merge a set of segments into a single segment
  - Policy specified by a `MergePolicy`
- You can explicitly invoke `forceMerge()` to merge segments

# Basic merge policy

---

- Segments are grouped into levels
- Segments within a level are roughly equal size (in log space)
- Once a level has enough segments, they are merged into a segment at the next level up

# Searching a changing index

---

```
Directory dir = FSDirectory.open(...);  
DirectoryReader reader = DirectoryReader.open(dir);  
IndexSearcher searcher = new IndexSearcher(reader);
```

Above `reader` does not reflect changes to the index unless you reopen it.

```
DirectoryReader newReader =  
    DirectoryReader.openIfChanged(reader);  
If (newReader != null) {  
    reader.close();  
    reader = newReader;  
    searcher = new IndexSearcher(reader);  
}
```

# Near-real-time search

---

This will update whether the writer's changes have been written yet or not.

```
IndexWriter writer = ...;
DirectoryReader reader =
    DirectoryReader.open(writer, true);
IndexSearcher searcher = new IndexSearcher(reader);

// Now let us say there's a change to the index using writer
writer.addDocument(newDoc);

DirectoryReader newReader =
    DirectoryReader.openIfChanged(reader, writer, true);
if (newReader != null) {
    reader.close();
    reader = newReader;
    searcher = new IndexSearcher(reader);
}
```

# QueryParser

---

- Constructor
  - `StandardQueryParser(Analyzer analyzer);`
- Parsing methods
  - `Query parse(String query) throws ParseException;`
  - ... and many more

# QueryParser syntax examples

Query expression	Document matches if...
java	Contains the term <i>java</i> in the default field
java junit java OR junit	Contains the term <i>java</i> or <i>junit</i> or both in the default field ( <i>the default operator can be changed to AND</i> )
+java +junit java AND junit	Contains both <i>java</i> and <i>junit</i> in the default field
title:ant	Contains the term <i>ant</i> in the title field
title:extreme –subject:sports	Contains <i>extreme</i> in the title and not <i>sports</i> in subject
(agile OR extreme) AND java	Boolean expression matches
title:"junit in action"	Phrase matches in title
title:"junit action"~5	Proximity matches (within 5) in title
java*	Wildcard matches for single terms
java~	Fuzzy matches for single terms
lastmodified:[1/1/09 TO 12/31/09]	Range matches

# IndexSearcher

---

- Methods
  - `TopDocs search(Query q, int n);`
  - `Document doc(int docID);`

# TopDocs and ScoreDoc

---

- **TopDocs** methods
  - Number of documents that matched the search  
`totalHits`
  - Array of **ScoreDoc** instances containing results  
`scoreDocs`
  - Returns best score of all matches  
`getMaxScore()`
- **ScoreDoc** methods
  - Document id  
`doc`
  - Document score  
`score`

# Scoring

---

- Original scoring function uses basic tf-idf scoring with
  - Programmable boost values for certain fields in documents
  - Length normalization
  - Boosts for documents containing more of the query terms
- `IndexSearcher` provides an `explain()` method that explains the scoring of a document

# Lucene 5.0 Scoring

---

- As well as traditional tf.idf vector space model, Lucene has:
  - BM25
  - drf (divergence from randomness)
  - ib (information (theory)-based similarity)

```
indexSearcher.setSimilarity(  
    new BM25Similarity());  
BM25Similarity custom =  
    new BM25Similarity(1.2, 0.75); // k1, b  
indexSearcher.setSimilarity(custom);
```